

3820

Cordless Linear Imager

The 3820 combines exclusive Adaptus® Imaging Technology 5.0 with Bluetooth wireless connectivity to provide class-leading performance and durability for retail and commercial cordless bar code reading.

In applications where operators must move about to read bar codes, cables become a limiting factor. They cause inefficiencies or safety and ergonomic concerns. Cable length often limits working range, resulting in an object being moved to the reader because the reader can't be taken to the object. With cordless bar code reading, operators have freedom of movement required to quickly, safely, and ergonomically read bar code data. With a 33 foot (10m) working range and 24 inch (61cm) read-range, the 3820 has the right combination of performance and features.

Having the right performance is only part of the solution; staying in service is just as important. The 3820 also has class-leading durability. It was designed to survive in real world mobile applications. Honeywell is committed to creating some of the most rugged products available, and the 3820 is another example of that commitment. With no moving parts and a robust housing design, the 3820 will easily provide years of service in retail and commercial environments, creating a favorable total cost of ownership.



Features

- **Superior Read Range:** Imaging technology now extends the read range out to 24 inches (61 cm) on the bar codes used in retail applications.
- **Fast and Aggressive Decode:** Even on poorly printed or damaged codes, the 270 scans per second scan rate and software digitizer quickly processes the data and transmits it to your application.
- **Wireless Connectivity:** Bluetooth v1.2 radio enables movement up to 33 feet (10m) from the base, and reduces interference with other wireless systems. Up to 7 imagers can communicate to 1 base, reducing the total cost of ownership.
- **Battery:** A long lasting, high capacity lithium ion battery provides 57,000 scans per full charge with no conditioning required. The battery is field-replaceable.
- **Durable:** Honeywell's solid state, no-moving-parts imager design withstands more than fifty 6 foot (1.8m) drops to concrete.
- **Unique Base Design offers the following features:**
 - A minimal footprint that is up to 33% smaller than major competitors', simplifying installation and leaving more counter space for customer service or other application needs.
 - Presentation scanning with a docked imager for efficient, hands-free bar code reading.
 - Host-powered interface and RF link; an exclusive Honeywell feature that extends the mobile capabilities of the 3820 by drawing power from a portable device for radio and host communications.

3820 Specifications

Performance

Illumination:	630 NM Visible Red LED
Receiving Device:	3648 element linear imager
Reading Distance:	From 1 in. (2.5 cm) to 24 in. (61 cm) on medium density codes
Reading Width:	7.5 mil code: 7 in. (18 cm) from nose, 6.6 in. (17 cm) wide 13 mil code: 16.5 in. (42 cm) from nose, 10 in. (25 cm) wide
Resolution:	5 mil. at 5 in. (13 cm) distance
Skew Angle:	±65°
Pitch Angle:	±65°
Minimum Symbol Contrast:	20%
Scan Rate:	Up to 270 scans per second
Decode Rate:	270 decodes per second

Wireless Technology

Frequency:	2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Bluetooth v. 1.2
Range:	33 ft. (10 m) typical
Data Rates:	720 Kbps
Security:	FIPS 140-2 (Certification Pending)

Battery (Lithium Ion)

Capacity:	1,800 mAh (minimum)
Number of Scans:	57,000
Expected Hours of Operation:	16 hours
Charge Time with 9 VDC External Power Supply:	4 hours for full charge from full discharge

Symbologies:	China Post, Codabar, Codablock F, Code 2 of 5, Code 11, Code 16K, Code 39, Code 32 Pharmaceutical (PARAF), Code 49, Code 128, EAN/JAN, IATA Code 2 of 5, Interleaved 2 of 5, Korea Post, Matrix 2 of 5, Coupon Code, MSI, Plessey Code, PosiCode, GS1 DataBar, Telepen, Trioptic, UPC-A, UPC-E, and ISBT 128 Concatenation (requires a paid license). 2005 Sunrise/GTIN compliant.
---------------------	--

Interfaces:	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, TTL level RS-232, wand emulation mode, TTL level Serial Wedge, and IBM 46XX retail terminals.
--------------------	---

Mechanical/Electrical

	3820 Scanner with Battery	2020 Base
Dimensions		
Weight:	9.2 oz. (261 g)	8.8 oz. (250 g) w/o cable
Height:	6.5 in. (16.5 cm)	3.1 in. (7.9 cm)
Power Requirements		
Input Voltage:	3.7 V internal battery	4.7 to 14 VDC (host) 8.5 to 9.5 VDC external power supply
Current Draw		125 mA max @ 5V (no charging) 100 mA max @ 12V (no charging) 825 mA max @ 12V (charging)

Environmental

	3820 Scanner with Battery	2020 Base
Sealing:	IP 41 (Water and Dust Resistant)	
Operating Temperature:	32° to 122°F (0° to 50°C)	32° to 122°F (0° to 50°C)
Storage Temperature:	-40° to 140°F (-40° to 60°C)	-40° to 140°F (-40° to 60°C)
Humidity:	up to 95%, non condensing	up to 95%, non condensing
Mechanical Shock:	Functional after 50 drops from 6 ft. (1.8 m)	Functional after 50 drops from 3.3 ft. (1 m)
Ambient Illumination:	0-76,000 lux	
ESD Protection:	Functional after 15 kV discharge	
Agency:	International: CB scheme to IEC60950-1 & IEC60825-1 Class 1 LED (3820). Bluetooth Qualified Design listed. USA: FCC Part 15 subpart C. UL listed to 60950-1. Canada: RSS-210. cUL listed to CSA C22.2 No. 60950-1-03. Europe: CE 1999/5/EC R&TTE Directive to EN55022, EN55024, EN61000-3-2, EN61000-3-3. 2006/95/EC Low Voltage Directive (2020). GS Mark: GS marked for I.T.E. safety. Mexico: NOM-NYCE, COFETEL. Australia/NZ: C-Tick mark.	
Warranty:	3 years (Note: battery warranty is 1 year)	

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Honeywell.



The 3820 Cordless Linear Imager has no affiliation with Honeywell branded batteries/chargers, which are exclusively distributed by Global Technology Systems pursuant to a license agreement.

Honeywell International Inc.
700 Visions Drive
PO Box 208
Skaneateles Falls, NY 13153-0208
www.honeywell.com/aidc

3820-SS Rev G 6/08
Copyright ©2008 Honeywell International Inc.

Honeywell